



Technical Specification of F360-YL

Product code	F360 YELLOW	Specification No.	IT/R/51
Product Description	POLYESTER ADHESIVE TAPE	Revision No.	4
UL File		Revision Date	03rd-Mar-2021
Test Method	IS 7809 PART II		Uncontrolled Copy
Remarks			
Sl. No.	Property Description	Units of Measurement	Standard Value
1	TEMPERATURE CLASS	Deg. C	130
2	TOTAL THICKNESS	mm	0.110 +/- 10%
3	TENSILE STRENGTH - MACHINE DIRECTION	Kgs/Cm	8 Minimum
4	ELONGATION AT BREAK - MACHINE DIRECTION	%	60 Minimum
5	ADHESION TO STEEL	Gms/Cm	220 Minimum
6	BREAK DOWN VOLTAGE - IS 2584 METHOD	kV	7.5 Minimum
7	HEAT CURING	--	30 mins. @ 130 Deg. C
8	COMPLIES WITH ROHS 2011/65/EU & 2015/863 DIRECTIVE	--	YES

Note:

All Statements, Technical Information and Recommendations are based on Test, we believe to be reliable and should not be taken to frame specifications. Before using the Tape the user shall determine the suitability of the product for his intended use.

Warranty and Liability : If the product supplied by Intek Tapes Pvt Ltd., is found to be defective within the shelf life period, Intek's sole obligation will be to replace the product or refund the purchase price.

Limitation of Liability : Intek shall not be liable for damages or loss arising out of using Intek's products whether direct, Indirect, incidental or consequential.

Report generated by System, Signature is not Required

◆ Intek Tapes Pvt. Ltd. Bangalore - 2023 19:44 20th-December -2023