

TECHNICAL DATSHEET


HOSE CLAMP WORM DRIVE



SPECIFICATION:

1. All material S.S.304
2. Strip thickness : 0.7mm
3. Strip width : 12.6mm
4. Screw head : 8mm

SR.NO	SIZE	MINIMUM DIAMETER MM	MAXIMUM DIAMETER MM
1	00	12	19
2	0	16	22
3	100S	19	25
4	0X	22	28
5	137S	25	35
6	1	28	38
7	1X	32	41
8	2A	32	48
9	2	38	54
10	2X	44	60
11	3	50	70
12	3X	60	80
13	4	70	85
14	4X	82	100
15	5	95	115
16	6	105	125
17	6X	125	155



TECHNICAL DATSHEET


HOSE CLAMP WIRE TYPE



SPECIFICATION:

1. All material S.S.304
2. Higher strength
3. Wire size as per table
4. Screw head as per table

SR.NO	SIZE MM	MINIMUM DIAMETER MM	MAXIMUM DIAMETER MM	WIRE DIAMETER MM	SIZE OF SCREW
1	17	14	18	1.5	5 X 20MM
2	19	16	20	1.5	5 X 20MM
3	22	18	23	1.5	5 X 25MM
4	32	26	33	2.0	5 X 35MM
5	35	27	36	2.0	5 X 35MM
6	38	31	39	2.0	5 X 40MM
7	43	35	44	2.0	5 X 45MM
8	45	37	46	2.0	5 X 45MM
9	52	43	54	2.5	6 X 60MM
10	65	57	67	2.5	6 X 65MM
11	75	65	77	2.5	6 X 70MM
12	93	84	96	3.0	6 X 70MM
13	100	90	102	3.0	6 X 70MM



TECHNICAL DATASHEET

HOSE CLAMP HEAVY DUTY



SPECIFICATION:

1. All material S.S.304
2. Higher strength
3. Higher Strip width provide more grip
4. Bolt suitable to sustain higher force

SR.NO	MINIMUM DIAMETER MM	MAXIMUM DIAMETER MM	STRIP WIDTH MM	STRIP THICKNESS MM	SIZE OF BOLT
1	68	74	25	1.5	10X75MM
2	74	80	25	1.5	10X75MM
3	80	87	25	1.5	10X75MM
4	88	96	25	1.5	10X75MM
5	91	100	25	1.5	10X75MM
6	105	115	25	1.5	10X75MM
7	120	128	25	1.5	10X75MM